

Technical product information for Sticky Notes products

Adhesive paper with special attributes for removable applications,

Facestock		Value / Tolerance	
Description	uncoated 100% recycling paper; Colors: pastel yellow, green, blue, pink		
Caliper	ISO 534	90 µm	± 3 µm
Basis weight	ISO 536	70 g/m²	± 3 g/m²
Credentials	Blue Angel certified		

Adhesive		Value / Tolerance
Denomination	Micro Tac waterbased, ultra-removable, microsphere adhesive	
Description	coarse dispersed acrylate, solvent free, excellent resistance to UV-light and ageing, suitable for multiple use and repositioning, sloughs residue-free from almost all undergrounds	

Technical application data	Value / Tolerance
Recommended application temperature	+ 20 °C
Service temperature	+10 °C to + 30 °C; 40 - 60 % rel. humidity
Shelf life at 20 °C, 50% R.H.*	2 years
* in non-opened original packaging	

No safety data sheet required as the goods aren't subject to specific labelling under current EU regulations. 02/07/2023

Warranty: UPM Raflatac self-adhesive film and paper products are manufactured according to highest quality standards and pass stringent quality controls before shipment. The wide range of different applications does not allow to test all possibilities of employment. All statements, technical information and recommendations are based on tests and practical experiences and believed to be reliable but do not constitute a guarantee or warranty. Preliminary tests are recommended for each new application. For any need of advise or technical support the UPM Raflatac technical department will be pleased to assist.