

Allied Telesis AT-XS916MXT-50 Géré L3 10G Ethernet (100/1000/10000) Gris

Marque : Allied Telesis

Code produit: 990-004943-50



Nom du produit : AT-XS916MXT-50

Allied Telesis AT-XS916MXT-50. Type de commutateur: Géré, Banc de commutateurs: L3. Type de port Ethernet RJ-45 de commutation de base: 10G Ethernet (100/1000/10000), Quantité de ports Ethernet RJ-45 de commutation de base: 12. Full duplex. Répertoire MAC: 16000 entrées, Capacité de commutation: 320 Gbit/s. Standards réseau: IEEE 802.1x, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3x, IEEE...

Management features		Security	
Switch type *	Managed	Loop protection	✓
Switch layer	L3	BPDU filtering/protection	✓
Quality of Service (QoS) support	✓	Authentication	MAC-based authentication
Web-based management	✓	Multicast features	
Traffic classification	✓	Multicast support	✓
ARP inspection	✓	Design	
System event log	✓	Rack mounting *	✗
Ports & interfaces		Stackable *	✓
Basic switching RJ-45 Ethernet ports quantity *	12	Product colour	Grey
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Performance	
SFP+ module slots quantity	4	Flash memory	96 MB
Network		Noise level	42 dB
Networking standards *	IEEE 802.1x, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3x, IEEE 802.3z	Power	
10G support *	✓	Number of power supply units	1
Port mirroring	✓	AC input voltage	100 - 240 V
Full duplex	✓	AC input frequency	47/63 Hz
IP routing	✓	Power consumption (max)	78 W
Flow control support	✓	Power over Ethernet (PoE)	
Link aggregation	✓	Power over Ethernet (PoE) *	✗
Spanning tree protocol	✓	Operational conditions	
VLAN support	✓	Operating temperature (T-T)	0 - 50 °C
Data transmission		Storage temperature (T-T)	-25 - 70 °C
Switching capacity *	320 Gbit/s	Operating relative humidity (H-H)	5 - 90%
Throughput	238 Mpps	Storage relative humidity (H-H)	5 - 95%
MAC address table *	16000 entries	Operating altitude	0 - 3000 m
Number of queues	8	Heat dissipation	270 BTU/h
Jumbo frames support	✓	Weight & dimensions	
Security		Width	323 mm
DHCP features	DHCP client	Depth	210 mm
Access Control List (ACL)	✓	Height	43 mm
IGMP snooping	✓	Weight	2.7 kg
SSH/SSL support	✓	Logistics data	
		Harmonized System (HS) code	85176990



0767035208077



767035208077

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAY-2025. Prints or copies of Information are only valid on the printed Publication date