

Epson EcoTank ET-16600

Marque : Epson

Famille de produit: EcoTank

Code produit: C11CH72401

Nom du produit : EcoTank
ET-16600

- Impression et numérisation ultra-rapides: Jusqu'à 25 ipm
- Coût par page ultra économique: Système de réservoirs d'encre économique
- Réservoir d'encre en façade simple d'utilisation: Bénéficiez de recharges simples avec les bouteilles d'encre perfectionnées
- Impression et connectivité mobiles: Wi-Fi, Wi-Fi Direct, Ethernet et applications d'impression mobiles gratuites²
- Conçue pour les entreprises: Multifonction A3+, 2 bacs A3 à chargement frontal 250 f., chargeur automatique A3 de 50 feuilles

EcoTank ET-16600

Epson EcoTank ET-16600. Technologie d'impression: Jet d'encre, Impression: Impression couleur, Résolution maximale: 4800 x 2400 DPI, Vitesse d'impression (couleur, qualité normale, A4/US Letter): 22 ppm. Copier: Copie couleur. Numérisation: Numérisation couleur, Résolution de numérisation optique: 1200 x 2400 DPI. Télécopier: Télécopie couleur. Taille de papier de série A ISO maximum: A3. Wifi. Impression directe. Couleur du produit: Noir



Printing		Input & output capacity	
Duplex printing mode	Auto	Auto document feeder (ADF) input capacity	50 sheets
Print technology *	Inkjet	Paper handling	
Printing *	Colour printing	Maximum ISO A-series paper size *	A3
Duplex printing *	✓	Paper tray media types *	Envelopes
Maximum resolution *	4800 x 2400 DPI	ISO A-series sizes (A0...A9) *	A3, A3+, A4, A5, A6
Print speed (black, normal quality, A4/US Letter) *	32 ppm	ISO B-series sizes (B0...B9)	B6
Print speed (colour, normal quality, A4/US Letter)	22 ppm	Envelopes sizes	10, DL
Print speed (ISO/IEC 24734) mono	25 ipm	Paper tray media weight	64 - 255 g/m ²
Print speed (ISO/IEC 24734) colour	12 ipm	Ports & interfaces	
Print speed (ISO/IEC 24734) black	25 ppm	Direct printing *	✓
Print speed (ISO/IEC 24734) colour	12 ppm	USB port	✓
Duplex print speed (black, normal quality, A4/US Letter)	16 ppm	Network	
Duplex print speed (colour, normal quality, A4/US Letter)	9 ppm	Wi-Fi *	✓
Duplex print speed (ISO/IEC 24734) mono	11.5 ipm	Ethernet LAN *	✓
Duplex print speed (ISO/IEC 24734) colour	6 ipm	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Duplex print speed (ISO/IEC 24734, A4) black	16 ppm	Security algorithms	64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP
Duplex print speed (ISO/IEC 24734, A4) colour	9 ppm	Mobile printing technologies	Epson Connect, Epson iPrint, Epson Email Print, Epson Remote Print, Apple AirPrint
Time to first page (black, normal)	5.5 s	Performance	
Time to first page (colour, normal)	8.5 s	Card reader integrated	✗
Borderless printing	✓	Design	
Copying		Product colour *	Black
Duplex copying *	✓	Market positioning *	Home & office
Duplex copying mode	Auto	Built-in display *	✓
Copying *	Colour copying	Display	LCD
		Display diagonal	10.9 cm (4.3")

Scanning		Design	
Duplex scanning *	✓	Touchscreen	✓
Duplex scanning mode	Auto	Control type	Touch
Scanning *	Colour scanning	Colour display	✓
Optical scanning resolution *	1200 x 2400 DPI	Power	
Scan technology	CIS	Power consumption (copying)	19 W
Scan to	Cloud	Power consumption (ready)	8.9 W
Scan speed (colour)	9 ppm	Power consumption (sleep)	0.8 W
Scan speed (black)	26 ppm	Power consumption (off)	0.2 W
Duplex scan speed (colour)	6 ppm	Energy Star Typical Electricity Consumption (TEC)	0.13 kWh/week
Duplex scan speed (black)	11.5 ppm	AC input voltage	220 - 240 V
Scan speed (black)	26 inch/min	AC input frequency	50 - 60 Hz
Scan speed (colour)	9 inch/min	System requirements	
Image formats supported	BMP, JPEG, TIFF, PNG	Windows operating systems supported	Windows 10, Windows 10 x64, Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows Vista, Windows Vista x64, Windows XP Professional x64, Windows XP
Document formats supported	PDF		Mac OS X 10.6 Snow Leopard
Fax		Mac operating systems supported	Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Server 2003 R2, Windows Server 2003
Duplex faxing	✓	Weight & dimensions	
Faxing *	Colour faxing	Width	515 mm
Fax transmission speed	3 sec/page	Depth	500 mm
Modem speed	33.6 Kbit/s	Height	350 mm
Fax memory	550 pages	Weight	20.7 kg
Fax memory	6 MB	Packaging data	
Auto-redialing	✓	Package width	558 mm
Speed dialling	✓	Package depth	590 mm
Fax speed dialling (max numbers)	200	Package height	440 mm
Fax forwarding	✓	Package weight	24.4 kg
Fax forwarding to	E-mail, Folder, PC	Quantity per pack	1 pc(s)
Error Correction Mode (ECM)	✓	Packaging content	
Features		Cartridge(s) included	✓
Number of print cartridges *	4	Included cartridge capacity (black)	4500 pages
Printing colours *	Black	Included cartridge capacity (CMY)	2800 pages
Country of origin	Indonesia	Cables included	AC
Replacement cartridges	T542120-S, T542320-S, T542220-S, T542520-S, T542420-S	Manual	✓
Input & output capacity		Logistics data	
Total number of input trays *	3	Harmonized System (HS) code	84433100
Total input capacity *	550 sheets	Pallet gross weight	0 g
Total output capacity *	125 sheets	Products per pallet	8 pc(s)
Paper tray 1 input capacity	250 sheets	Pallet weight (UK)	0 g
Paper tray 2 input capacity	250 sheets	Products per pallet (UK)	8 pc(s)
Auto document feeder (ADF)	✓	Other features	
		Printing method	Epson PrecisionCore
		Compatible operating systems	Mac OS X 10.6.8 or later, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 Bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 Bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later

Other features	
Ink drop	3.8
Fax polling	✓
Print head nozzles	800 nozzles black, 256 nozzles per colour



8715946667836

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-MAR-2025. Prints or copies of Information are only valid on the printed Publication date